

PRISMA ZX

SAE 75W/80 GL-4+5

Synthetic performance oil for manual gearboxes and axle drives. API GL-4+5.

Description

PRISMA ZX SAE 75W/80 is a synthetic, low-friction oil for a multitude of uses. Guarantees optimum lubrication over a large temperature range, even under high loads, both in synchronised and unsynchronised manual gearboxes and axle drives.

Advantages

- optimum protection against wear
- excellent oxidation and shear stability
- excellent viscosity / temperature behaviour
- good anti-foaming behaviour
- very low pour point

Field of application

PRISMA ZX SAE 75W/80 has been specially developed for front-wheel-drive vehicles. The formula guarantees perfect synchronisation in manual gearboxes and the reliable lubrication of the integrated differential. The low viscosity guarantees excellent cold-shifting behaviour. PRISMA ZX SAE 75W/80 is ideal for vehicles such as VW/AUDI, RENAULT, PEUGEOT and CITROËN.

Notes

Please adhere to the manufacturer's instructions.

Specifications

API GL-4/5

Technical data

Properties	Unit	Test according to	Values
Colour			yellow
Density at 20 °C	g/cm³	ASTM D4052	0.861
Viscosity at 40 °C	mm²/s	DIN 51562-1	49.9
Viscosity at 100 °C	mm²/s	DIN 51562-1	9.4
Viscosity index		DIN ISO 2909	175
Pourpoint	°C	ASTM D5950	-45
Flash point C.O.C.	°C	DIN EN ISO 2592	>220
Brookfield	°C / mPa·s	ASTM D 2983	-40 / 32500
Timken-Test	N	DIN 51434-3	3600

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.



MOTOREX AG
Bern-Zürich-Strasse 31
CH-4901 Langenthal
Tel. +41 (0)62 919 75 75
info@motorex.com, www.motorex.com